



MFRS OF : AUTOMOTIVE & INDUSTRIAL GREASES,
OILS & SPECIALITIES

PRODUCT DATA SHEET

CLAY BASE MOLY GREASE

Description:

Clay Base Moly Grease is smooth, homogeneous non soap grease formulated with highly refined petroleum oil, organically modified clay and fortified with solid molybdenum disulfide powder as solid lubricant.

Key Features :

- ⇒ High drop point
- ⇒ Withstands high temperatures and high loads

Applications:

Clay Base Moly Grease is recommended for lubrication of antifriction and plain bearings in industrial applications operating at high temperatures and high loads. They are used in steel plants, power plants and other industrial applications.

TYPICAL DATA

TEST	TEST METHOD	DATA
NLGI GRADE	-	2
Appearance	Visual	Smooth homogeneous
Color	Visual	Blackish gray
Penetration, 60 strokes	ASTM D-217	265-295
Drop Point, deg C	ASTM D-2265	>280
Four Ball Weld Load, Kgs.	ASTM D-2596	200
Operating temperature range, deg C	-	-10 to 160

Health and Safety:

Based on the information available, this product is not likely to pose any adverse effects on health provided it is used as per the recommendation. For more information refer MSDS. For disposal, check local regulations and take care to protect the environment.

The data and information in this is based on our general experience and knowledge. It is given to reader for possible applications. It is the responsibility of the user to use the product safely

Standard Greases & Specialities Pvt. Ltd.

Manufacturers of Automotive Industrial Grease & Specialities

REGISTERED OFFICE : 101, Ketan Apartments, 233, R.B. Mehta Marg, Ghatkopar (E), Mumbai 400 077.(India) ' 2501 3641 • Fax : 2510 0384